

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**  
Das Original

## Self-levelling crossline laser

### ALC 3/1-Basic

Order number 409.243



#### Self-levelling crossline laser

- + With one horizontal and two vertical laser lines at a 90° angle plus plumb, can be switched individually
- + Plumb function
- + The exceptionally bright laser lines are still highly visible even in poor light conditions
- + Self-levelling
- + Optical warning signal when self-levelling range exceeded
- + Self-levelling which can be switched off
- + Simple On-button operation
- + Transportation lock
- + 1/4" thread for tripod
- + Ideal for aligning the framework

#### Technical attributes

|                          |                                    |
|--------------------------|------------------------------------|
| Number of lines          | 1 horizontal/2 vertical plus plumb |
| Visible area lines       | 90°                                |
| Precision                | ± 0.3 mm/m<br>(plumb ± 0,6 mm/m)   |
| Self-levelling range     | ± 4 °                              |
| Max. working range       | 20 m / plumb 5 m                   |
| Operation duration       | 6 h                                |
| Temperature range        | -5° - +50 °C                       |
| Laser class              | 2                                  |
| International Protection | IP 54                              |
| Weight                   | 0,58 kg                            |

#### Standard equipment

|   |         |
|---|---------|
| 1 wall bracket magnetic WB- 428.167 M/S 1/4 ALC-Basic |         |
| Batteries 3x AA                                       | 1 set   |
| 1 carrying bag  | 1 piece |