



# MultiTrack

## THE UNBREAKABLE ORIGINAL

### **RAPID INSTALLATION**

Lay approximately  
50 mats per hour.\*

### **TOUGH**

Virtually indestructible HDPE  
polymer supports all vehicle types.

### **EASY TO HANDLE**

Lightweight 39kg mats easily  
handleable with two workers.

### **MULTI-TREAD**

Roadway, Walkway and Smooth tread  
options cater for various vehicular and  
pedestrian needs.

### **ENVIRONMENTALLY FRIENDLY**

Made from 100% recycled  
plastic and fully recyclable.

### **GUARANTEED UNBREAKABLE**

Lifetime guarantee against breakage by  
vehicles up to 120 tonnes (T&Cs apply).

**NO CRANES OR  
SPECIALIST  
LIFTING  
EQUIPMENT  
NEEDED!**

***\*FAST, EASY, ECONOMICAL***  
***Install approximately 50 mats***  
***per hour with a team of***  
***4 plus forklift driver.***

[www.ground-guards.co.uk](http://www.ground-guards.co.uk)

**+44 (0) 113 267 6000**

[info@ground-guards.co.uk](mailto:info@ground-guards.co.uk)

**Ground-Guards®**





# MultiTrack

**THE UNBREAKABLE ORIGINAL**



Watch this short video to see MultiTrack in action.



MultiTrack mats are the strongest in their category



Mats are easily moved using a HandiHook



Standard no-tools joiners quickly clip the mats together



Low profile joiners for walkways plus bolted joiners



SafeStore stillages hold 25 mats

**Material:** Special blend of HDPE recycled plastic, fully recyclable

**Overall Size:** 2435 x 1215 x 13mm (plus treads)

**Surface Area:** 2.95m<sup>2</sup>

**Weight:** 39kg

**Tread Options:** Roadway, Walkway and Smooth, or a combination

**Connectors:** 10 joining points. A choice of standard clip joiners, low profile joiners or bolted joiners, plus anchor pins

**Packed in:** Stillage of 25 mats

**Stillage Pack:** **Weight:** 1105kg  
**Dimensions:** 2550 x 1260 x 900mm

**Fire Rating:** UL94 HB

**Slip Testing:** BS7976 part 2

**Deflection:** Tested on varying CBR ground conditions using a 300mm diameter steel platen with 6 tonnes load to simulate the pressure of an HGV wheel

**Ground CBR 11.35%:** Deflection 17.68mm

**Ground CBR 8.58%:** Deflection 20.41mm

**Ground CBR 4%:** Deflection 22.00mm



## Guarantee:

MultiTrack temporary roadway mats are guaranteed for life against breakage up to 120 Tonnes UDL (Uniformly Distributed Load).

It is the user's responsibility to assess the load-bearing capacity of the ground, and to only operate vehicles within the weight that the ground is capable of safely supporting. Ground-Guards Ltd accepts no liability whatsoever for any damage, loss or injury arising from the ground conditions on which these products are used.

MultiTrack mats are not suitable to use for bridging purposes. Damage caused by mechanical equipment (e.g. cuts by digger buckets) or sharp protrusions beneath the mats is not covered by this guarantee.



[www.ground-guards.co.uk](http://www.ground-guards.co.uk)

**+44 (0) 113 267 6000**

[info@ground-guards.co.uk](mailto:info@ground-guards.co.uk)

**Ground-Guards®**